

LEZARD

色譯

Surface Finishes



The STP Series is an easy-to-apply water-based paint with stone chips & other additives for hard-wearing stone-like effects with glimmer or glitter.

STP 系列由水性塗料添加石顆等物料而成，能輕易製作類似石飾面的效果，更可按喜好加入亮片增添貴氣。

STP

PRODUCT DATA SHEET 產品資料

PRODUCT DESCRIPTION 產品介紹	A water-based decorative wall coating for hard-wearing stone-like effects with glimmer or glitter	帶有石飾面效果的水性塗料，耐用、防刮和衛生
TEST DATA 測試數據 Anti-Microbial Preservation 抗菌力 Fire Test 防火測試	<u>Scrub Resistance</u> ASTM D2486: 1,150 cycles ISO 2812: Class 2 - washable <u>Stain Resistance (ASTM D1308)</u> Coffee 4, red wine 4, vinegar 5, tomato sauce 5, mustard 3, strawberry preserve 5 (1= poor 5 = excellent) <u>Mould resistance (ASTM D3273)</u> 10/10/10 <u>Mildew resistance (ASTM D3274)</u> 10/10/10 (1= poor 10 = no growth) <u>Anti-Fungal Activity</u> No visible growth <u>Anti-Algal Activity</u> No visible growth <u>Anti-Bacterial (JIS Z2801)</u> E.Coli, MRSA, Salmonella: No bacteria survived <u>ASTM E84: Class A</u>	<u>耐磨性</u> ASTM D2486: 1,150 次 ISO 2812: 第二級 (可洗刷) <u>抗污性 (ASTM D1308)</u> 咖啡 4, 紅酒 4, 醋 5, 茄汁 5, 芥末 3, 草莓果醬 5 (1=劣 5 =優) <u>防黴性 (ASTM D3273)</u> 10/10/10 <u>防霉性 (ASTM D3274)</u> 10/10/10 (1=劣 10 =沒有增生) <u>抗真菌活性</u> 沒有明顯增生 <u>抗藻活性</u> 沒有明顯增生 <u>抗菌性 (JIS Z2801)</u> 大腸桿菌, 金黃葡萄球菌, 沙門氏菌: 沒有細菌存活 ASTM E84: "A"級
VOC CONTENT 低揮發性有機物含量	<u>ASTM D3960 (USA EPA <250g/l)</u> 67g/l <u>BS ISO EN 11890-2</u> EU limit for this product (cat A/I): 200 g/l (2010). This product contains max 10g/l VOC	ASTM D3960 (美國環保署 <250 克/升) 67 克/升 BS ISO EN 11890-2 歐盟對於此產品的限制 (類別 A / I): 200 克/升 (2010)。 此產品每升最多含 10 克低揮發性有機物
COVERAGE RATES 覆蓋率	4-5m ² /litre (two coat application)	4-5 m²/公升 (兩層)
MANUFACTURER 生產商	Manufactured in the UK by Armourcoat Ltd Mixed & Prepared by Lezard Design & Contracting Co., Ltd in Hong Kong	由藝紋塗 (Armourcoat Ltd) 於英國製造、色譯 (Lezard Design) 於香港調製及生產
HEALTH & SAFETY 健康與安全	Non-toxic. Refer to Material Safety Data Sheet for further information.	無毒。請參閱《材料安全數據表》查看更多信息。
SUITABLE SUBSTRATES 合適的底材	Can be applied to our recommended substrates which should be clean, dry, firm, true, will not crack and are correctly prepared. The best substrates to work on are taped and jointed plasterboard and freshly plastered walls that are fully dry. Tactite can be applied to existing painted surfaces provided that the paint is well adhered to the wall.	可以應用於我們建議的底材，最好使用已完成夾口紙帶的石膏板，以及批盪已完全乾透的牆。 如希望直接在現有的牆上使用觸藝塗 (Tactite)，須確保現有的油漆能牢固地粘附在牆壁上，且是清潔、堅固、平整及不會出現裂痕。
STORAGE 儲存	Store in good dry conditions between 5 – 25°C. Protect from frost, sunlight and sources of direct heat. Keep container sealed when not in use. Shelf life in an unopened container under correct storage conditions is 12 months from date of manufacture.	存放在 5 – 25°C 的乾爽環境下。避免霜凍、避免陽光直射和直接接觸熱源。不使用時須密封容器。若妥善儲存，未開封的產品保質期為生產日起 12 個月。



[Armourcoat PRC Sole Agent \(including Hong Kong & Macau\)](#)

[藝紋塗 Armourcoat 獨家代理商 \(中國內地、香港及澳門\)](#)

[Lezard Design & Contracting Co., Ltd. 色譯藝術裝飾有限公司](#)

Unit 5B, Cheung Wah Industrial Building, 10-12 Shipyard Lane, Quarry Bay, Hong Kong

香港鯉魚涌船塢里 10-12 號長華工業大廈 5 樓 B 室

Tel 電話: (852) 2591 1268 | Fax 傳真: (852) 2892 0182

Email 電郵: info@lezard.com.hk | URL 網址: <http://www.lezard.com.hk>

Manufacturer 生產商: **ARMOURCOAT Limited 藝紋塗**
 The World's Leading Manufacturer of Surface Finishes
 領先的裝飾塗料廠家

ARMOURCOAT
 SURFACE FINISHES